



**TW202-IP**  
High Definition IP Camera

**Fusion Mount.  
Versatile Design.  
Superior Imaging.**



<b>Video</b>	
Imaging Sensor:	2 MP 1/2.8" CMOS
Minimum Illumination:	0.05Lux(Color Illumination), F1.2
Resolution:	1920 x 1080 / 1280 x 720 / 640 x 360 / 704 x 567 / 640 x 360 / 320 x 180
Effective Pixels	2.43M effective pixels
Wide Dynamic Range	Yes - Wide Dynamic Range ≥80db
Voltage:	POE - 12v nominal
Data Stream:	ONVIF Profile S, v2.4
Operating Temperature:	-40°F to +158°F, (-40°C to +70°C)
Compression	H.264 Main Profile, H.264 Baseline Profile, MJPEG/JPEG Baseline
Bit Rate	512Kbps to 8 Mbps
Dual Stream	Main Stream: 1920 x 1080 / 1280 x 720 / 640 x 360 Sub Stream: VGA/WD1/D1/QVGA/CIF @30FPS HTTP, DDNS, DHCP, PPPoE, RTSP, RTP, RTCP
Protocols	ONVIF Profile S - 2.4
S/N Ratio:	≥48db
Power Consumption:	≤ 2.5W
Operating Humidity:	Less than 90% (Non-Condensing)


Electronic Shutter:	1/30 Second - 1/10000 Second
Gamma Correction:	0.45
AGC:	Auto
White Balance:	Auto

<b>Audio</b>	
Audio Options	Integrated Mic with Noise Suppression or External Line Level Audio Input
Audio Format	G711a/G711u/G726

<b>Package</b>	
Cabling Connection	Gatekeeper TW camera housing 13.8" (35 cm) long: RJ-45 Female
Exterior Dimensions	4.8" (L) x 3.0" (H) x 1.5" (W) 121.6mm(L)*75mm(H)*39mm(W)
Available Lenses	2.8mm, 4mm, 8mm M12 Fixed aperture F1.8
IP Rating	IP 53
Weight	1.1lbs (500g)

**Camera Placement**

Recommended camera placement and field of view:



Distributed By:

Specifications subject to change without notice.

**GATEKEEPER**

Simple Video Management Solutions

Gatekeeper Systems, Inc.  
www.gatekeeper-systems.com  
sales@gatekeeper-systems.com  
Toll Free: 1.888.666.4833

#301-31127 Wheel Avenue  
Abbotsford, BC V2T 6H1  
Tel: 1.604.864.6187  
Fax: 1.604.864.8490